

瑞士航太級低慣量、低衝擊馬達電動起子 / 氣吸式電動起子

瑞士馬達保證3年1000萬次
3C產業最佳選用品

Swiss aviation grade motor, low inertia and low impact electric screwdriver / Vacuum pick up electric screwdrivers

IT'S VERY WELL
MADE IN TAIWAN

低壓直流馬達驅動型（附電源控制器）
Low voltage DC motor driving (with controller)

可訂製ESD防靜電型
ESD type is available for ordering.



特點 Feature

- 超迷你精準耐用長壽命設計
直徑φ26mm全長158mm世界最小體積，重量只有187g、耗電6W，全機六只傳動軸承，徹底降低機械磨耗，更能提高扭力精準度及降低起子頭搖擺度。
 - 終生使用設計，一支抵用他牌數支
三年1000萬次以上終生耐用性設計，瑞士馬達至少可連續運轉2萬小時(約可使用10年以上)。並搭配長壽命設計可達1000萬次白金煞車開關裝置。
 - 本產品可適用於無塵室，並通過SGS無塵室CLASS-10等級測試。
- The electric screwdriver is very compact, accurate and durable.
Design not only in the most compact body of diameter 26mm, overall length 158mm and weight 187g but the lowest power consumption 6w in the world. The 6 bearing are inbuilt in the hammer casing to reduce the anvil friction and bit vibration and to improve the output torque precision.
 - The electric screwdriver can last through a lifetime; it outlasts several electric screwdrivers of other brand.
The everlasting durability is designed with 10 million times in use in three years (The Switzerland patented motor permits continued operation at least 20,000 hours (about 10 years operation). The service life of the contact point withstands 10 million on and off contacts.
 - This product can be used in the clean room. It has passed SGS Clean room Class-10 test.


槓桿式 Lever start type · 快速式 High speed type (S) · 氣吸式 Vacuum pick up type (A)

機種名 Model No.	輸出扭力範圍 Torque range		適用電源控制器 Available controller	無載轉速(±10%) No Load Speed (rpm)	適用螺絲 Available screw	
	kgf-cm	lbf-in			機械牙徑 Machine screw φ	自攻牙徑 Tapping screw φ
ASA-S1000M ASA-S1000MA	0.15~1.0	0.13 ~ 0.87	APM-302B APM-302B AM-55 AM-65	150-300 350-600 150-350 350-600	1.0 ~ 1.8mm / 0.04 ~ 0.07in	0.6 ~ 1.4mm / 0.02 ~ 0.05in
ASA-S2000M ASA-S2000MA	0.3 ~ 2.0	0.26 ~ 1.7	APM-302B AM-65	650-1000	1.0 ~ 2.2mm / 0.04 ~ 0.09in	1.0 ~ 2.0mm / 0.04 ~ 0.08in
ASA-S2500M ASA-S2500MA	0.4 ~ 3.0	0.35 ~ 2.6	APM-302B AM-65	450-700	1.0 ~ 2.6mm / 0.04 ~ 0.10in	1.0 ~ 2.0mm / 0.04 ~ 0.08in
ASA-2000M ASA-2000MS	0.3 ~ 2.0	0.26 ~ 1.7	APM-302B AM-65	450-700 700-1000	1.0 ~ 2.2mm / 0.04 ~ 0.09in	1.0 ~ 2.0mm / 0.04 ~ 0.08in
ASA-2000MA ASA-2000MSA	0.3 ~ 2.0	0.26 ~ 1.7	APM-302B AM-65	450-700 700-1000	1.0 ~ 2.2mm / 0.04 ~ 0.09in	1.0 ~ 2.0mm / 0.04 ~ 0.08in
ASA-3000M ASA-3000MS	0.5 ~ 5.0	0.43 ~ 4.3	APM-302B AM-65	400-600 700-1000	1.0 ~ 2.6mm / 0.04 ~ 0.10in	1.0 ~ 2.3mm / 0.04 ~ 0.09in
ASA-3000MA ASA-3000MSA	0.5 ~ 5.0	0.43 ~ 4.3	APM-302B AM-65	400-600 700-1000	1.0 ~ 2.6mm / 0.04 ~ 0.10in	1.0 ~ 2.3mm / 0.04 ~ 0.09in
ASA-4000M ASA-4000MS	1.0 ~ 6.0	0.87 ~ 5.2	APM-302B AM-65	400-600 700-1000	1.4 ~ 2.6mm / 0.06 ~ 0.10in	1.4 ~ 2.3mm / 0.06 ~ 0.09in
ASA-4000MA ASA-4000MSA	1.0 ~ 6.0	0.87 ~ 5.2	APM-302B AM-65	400-600 700-1000	1.4 ~ 2.6mm / 0.06 ~ 0.10in.	1.4 ~ 2.3mm / 0.06 ~ 0.09in

適用電源控制器 Available controller


外觀 Outline	機種名 Model No.	工作電壓(AC) Operating vol.	輸出電壓(DC) Output vol.	體積(mm) Dimension	重量(g) Weight	可操作起子數 Drivable	安規認可 Approval by
	APM-202B	100 ~ 240V	9 ~ 19V 可調式 (Adjustable)	172X84X46	380	1 screwdriver	CB,CE, UL(CUL), ROHS,REACH KC,FCC,UKCA
	APM-302B 軟式啟動 (Soft start)	100 ~ 240V	20 ~ 30V 可調式 (Adjustable)	172X84X46	380	1 screwdriver	CB,CE, UL(CUL), ROHS,REACH KC,FCC,UKCA
	AM-55	100 ~ 240V	9 ~ 15V 可調式 (Adjustable)	172X84X61	450	1 screwdriver	CB,CE, UL(CUL), ROHS,REACH
	AM-65	100 ~ 240V	20 ~ 30V 可調式 (Adjustable)	172X84X61	450	1 screwdriver	CB,CE, UL(CUL), ROHS,REACH

槓桿式尺寸圖 Dimension



工作電壓 Power Source	30VDC 最大/MAX
扭力精度 Torque Accuracy	極精準 High precision
扭力調整 Torque Setting	無段式 Stepless
重量 Weight	迷你型 Mini type 187 / 290g，標準型 Standard type 380 / 430g
長度 Length	迷你型 Mini type 158 / 198mm，標準型 Standard type 208 / 242mm
握持直徑 Grip diameter	迷你型 Mini type 26mm，標準型 Standard type 33.5mm
適用起子頭 (選購品)	φ4，6.35(1/4") 六角對邊 hex shank
Available bit size (optional)	

輸出扭力曲線表 Torque Curve



ASA 瑞士馬達電動起子 (彎90°轉接頭) Swiss motor electric screwdrivers (Angle attachment)

超微型彎90°轉接頭 (業界唯一獲得Apple認證的產品，並使用於iPhone及iPad生產線)
Ultra-miniature angle attachment (The only one which wins the identification of APPLE Company among all other competitors in business and being applied to IPHONE & IPAD's production line.)



瑞士原裝進口低慣性、低衝擊馬達

瑞士專利馬達耗電、衝擊、慣量只有市售馬達1/10。
對細小螺絲扭力精準度以及防止螺絲鬆動特別有效。


Its motor, made and imported from Switzerland, is characterized with low inertia and low impact.

Switzerland patented motor, its power consumption, impact and insert momentum are 1/10 of the conventional motors. Very effective for tightening the fine screws with precise torque and loosening free.



搭配10um黃金煞車開關系統，
壽命可達1000萬次以上。

Adopts 10um gold plating switch to raise the switch life upto 10 million times.



創新專利

超微型彎90°轉接頭直徑僅為5mm，適用於精密螺絲鎖付工作。

New Patent

The diameter of the ultra-miniature angle attachment is only 5mm. Suitable for precise screw fastening operations.

